

# B Field Maps and B-dot Calibration

Francisco Yumiceva

---

MINOS Collaboration Meeting

March 18, 2005




- **B-Field Maps:**
  - Status of field maps.
  - BH Variations per Plane.
  - End Effect Model.
- **B-dot Calibration and Measurements.**

# B-Field Maps



- FEA is run by Bob Wands who is working part time.
- Two maps are produced for each plane: one for each layer.




- The map used in reconstruction is the averaged field map.

# B-Field Maps (II)



## B-Field Map 201

- Constant slot width of 0.2 mm.
- Air gap between layers has a width of 0.2mm
- Current at 15 kA-turns.




# B-Field Maps (II)




## B-Field Map 202 (last map)

- Variable slot width: from 6mm at 4m to 0.25 mm near the center of the plane accordingly to  $6/64 \cdot r^3$
- Air gap between layers has a width of 0.5mm
- Map of the ears included.
- Current at 15 kA-turns.



## B-Field Map 203




- Map extended to +- 4.6m in x axis and +- 4.2 in y axis.
- Map in MINOS coordinates.
- Current at 15.2 kA-turns (80 A x 190 turns).
- $|B|$  module increased by < 0.5%.



# BH Variations per Plane



- The B-field maps use steel MS-10360 (MINOS steel).






- Maximum difference of 8% with LDJ steel compared to MINOS steel.

# BH Variations per Plane



- The B-field maps use steel MS-10360 (MINOS steel).




- Maximum difference of 8% with LDJ steel compared to MINOS steel.


# End Effects Model



*Front View*




*Isometric View*



*Twelve Plane Model*















# End Effects Model (II)




# End Effects Model (III)




Scale



# End Effects Model (IV)




*End Model Mesh*



*Mid-Detector Model Mesh*

$$\Delta |B| = |B(\text{map 203})| - |B(\text{map 203 coarse})|$$



# B-dot Calibration



## Software:


- Many bugs fixed (e.g. automatic reverse of switch).
- Active development of code (LabView).
  - ADC corrections.
  - Inverted polarization.
  - Optimization of step currents and time delays.
  - Writing data.
- Working on master/client servers.
- Computers configuration fixed.

## Hardware:


- PC moved around because of bad PCI cards.
- Trigger wires connections finished.
- Loose connections fixed.
- Few broken wires found. (it's being fixed).

# B-dot Calibration (II)


- We want to estimate the average BH changes per plane -> interested in changes of maximums and minimums in the BH curves.



**Drift**



**Drift  
Reduced**





## B-Field Maps:

- Map 203 available for tests. (no significant differences from 202).
- Working on a parametrized model for End Effect model and BH variations ( $B \rightarrow B'$ ).
- Next maps: new map for ND and supermodule gap model.

## B-dot Calibration:

- FD and ND code will be the same.
- Fixing problems before the next available time to test system. (Two days available next week).
- Working on the software problems (ADC corrections and data recording).
- Few hardware issues still pending but we can live with those for the moment.
- Trying to have master/client servers up and running for next test. We can run the system manually if this feature is not available.